

IMP 4733 CONTACT CEMENT

May be brushed on or sprayed. Adheres Acoustiblok™ to itself, wood, metal & most other surfaces. Apply to each side. The two surfaces need to be pressed together while tacky. The time duration of a tacky surface depends on temperature & humidity. Use manufacturer's instructions on product.

Available through Acoustiblok™

Price per 5 gallon bucket (FOB Tampa, Florida)

1 to 3	\$229.00
4 to 15	\$209.00
16 & up	\$199.00

IRON GRIP™ ONE SIDED TAPE 2"X60YD

A 2" wide tape specifically formulated to work with the "Acoustiblok" sound deadening material. 2.0 mil (51 microns) Top-Coated Gloss. Adhesive is designed to permanently bond to the most demanding surfaces including textured and contoured surfaces, plastics and printed metals. U.L. recognized and CSA accepted.

Available through Acoustiblok™

<u>Qty</u>	<u>Price</u> (FOB Tampa, FL)
1 to 3	\$29.95 per roll
4 to 23	\$25.95 per roll
23 up	\$24.95 per roll

Environmental Performance

The properties defined are based on a four hour immersion at room temperature unless otherwise noted.

<u>Chemical</u>	<u>Appearance</u>
Isopropyl Alcohol	No change
Detergent	No change
Engineer Oil at 250°F (121°)	No change
Water for 48 hours	No change

Temperature Resistance: 300°F (149°C) for 24 hours: Slight discoloration and shrinkage.
-40°F (-40°C) for 10 days: No change noted

Humidity Resistance: 24 hours at 100°F(38°C) and 100% relative humidity: No change noted.